

## **STARPORT 700 CONFIGURATION PROCESS**

The following steps instruct the dealer on how to configure the StarPort 700 interface to work with Globalstar data ready satellite products.

### **IMPORTANT: For Globalstar Authorized Dealers ONLY DO NOT COPY OR DISTRIBUTE TO END USER CUSTOMERS**

Please be advised that the interface **MUST** be set up to work with either the GSP-1600 Handheld Phone or the GSP-2900 Fixed Unit. NOTE: Both interfaces can also be used with the GCK-1410 car kit and GSP-1620 SDM. In both cases, set up the interface as if you are using it with a GSP-1600.

Here are the steps for setting up the interface:

1. Place the three-step **ON/OFF** switch located on the right side of the unit, to the middle position and wait for “*LED Number 2*” (located just below the Globalstar logo) to be on solid.
2. Press **Config/Select (the Select Key)**, enter pin code **1234** (enter numbers slowly) and press **Select**.
3. Cursor down to “*Default*” and press **Select**.
2. Cursor down to “*gstar*” for the GSP-1600 mobile OR “*gstar\_fixed*” for the GSP-2900 and press **Select**.
3. Enter pin code **1234** and press **Select**.
4. Unit will now display “*copy new config*” and switch back to the config screen. You have now completed the configuration process. Press **Cancel** to return unit to normal operating mode.

**If you have any questions please contact your local Globalstar Distribution Manager or Globalstar Customer Care at 1-877-452-5782 for more information.**

