

Globalstar FAU-200 Fixed Phone



Anyone living in or running a business from a remote area will appreciate the unparalleled connectivity of the FAU-200. The Globalstar FAU-200 Fixed Phone is the ideal cost-effective solution to access the coverage and reliability of Globalstar satellite phone service. For commercial or personal purposes, the FAU-200 provides high-quality, voice-only transmissions to remote businesses, communities and dwellings.

The FAU-200 delivers digital call quality, with virtually no voice delay. A natural fit for commercial and industrial sites that require day-to-day voice communications, the Globalstar FAU-200 is also a must for vacation properties and remote communities.

FAU-200 ADVANTAGES:

Custom Installation Configurations

Installation of the FAU-200 is quick and simple. The weatherproof unit can be mounted at any convenient outdoor location with an unobstructed view of the sky. The Globalstar FAU-200 can be installed anywhere you need the coverage and reliability of Globalstar's satellite network.

Simple Antenna Set-up

The fixed, omnidirectional antennas mean greater reliability. No aiming or calibration are required and there are no moving parts to break or wear out.

STANDARD TELEPHONE EQUIPMENT COMPATIBILITY:

The FAU-200 supports up to three phone jacks on a single phone line. The connection from the Fixed Antenna Unit to the telephone equipment can be as long as 800 ft (244 m). Use your Globalstar FAU-200 with any off-the-shelf CSA-approved phone (sold separately), including:

- Standard Handsets
- Desktop Speakerphones
- Cordless Phones
- Analog PABX Systems

FAU-200 INCLUDES:

- FAU Module
- Power Supply and Connection
- 50 ft (15 m) Power Cable
- Telephone Interface (NID) Box
- User Documentation Package
- TX Antenna
- RX Antenna
- Installation Handbook
- Telephone Handset and RJ-11 Cable not included

Visit Globalstar at www.globalstar.com for service plan and coverage details.



Globalstar FAU-200 Fixed Phone

TECHNICAL SPECIFICATIONS FAU-200 FIXED PHONE

COMPONENT

OPERATIONAL

NON-OPERATIONAL

FAU-200

Temperature

-22 to +140°F (-30 to +60°C)

-22 to +158°F (-30 to +70°C)

RF Power Output

2 watt maximum (+33dBm)

Power Consumption

50 watt maximum at 48 VDC nominal input voltage

Dimensions

20.5 in (52 cm) H x 11.9 in (30.5 cm) W x 6.9 in (17.5 cm) D

Weight

16.1 lbs (7.5 kg)

ANTENNAE

Temperature

-22 to +140°F (-30 to +60°C)

-22 to +158°F (-30 to +70°C)

TELEPHONE INTERFACE BOX

Temperature

-22 to +140°F (-30 to +60°C)

-22 to +158°F (-30 to +70°C)

Dimensions

6 in (15 cm) H x 3.2 in (8 cm) W x 2.1 in (5 cm) D

Weight

1.2 lbs (0.5 kg)

ADDITIONAL INFORMATION:

- Voice service only
- Roaming is not available with the FAU-200
- All standard Service Price Plans apply
- All standard Terms and Conditions apply
- All standard fees apply

www.globalstar.com

Some conditions apply. Rates for minutes based on individual price plan. Coverage may vary. Specifications subject to change without notice. Ask your local Globalstar Authorized Dealer for complete pricing and coverage information. Or see complete details at www.globalstar.com. Globalstar USA LLC. © 2004. All rights reserved. 461 So. Milpitas Blvd., Building 5, Milpitas CA, 95035 USA, P: 1.877.728.7466, F: 408.933.4100. Please see complete details of Globalstar service in the Terms and Conditions on our website, www.globalstar.com

September 2004 FAU-200 US

